

DataSheet

ASP-65 ANTI-STATIC PANEL WIPE



A low VOC, non-hazardous degreaser for surface preparation prior to painting.

Features:

- Anti static, anti silicone panel wipe
- Effective/efficient degreaser for surface preparation of metal and plastic surfaces prior to painting
- Low VOC content
- Excellent degreasing properties
- Suitable for use on solvent sensitive plastics

Benefits

- Provides a powerful degreasing action that avoids any attack on existing paint films/surfaces
- Compatible with most paint systems including water-based systems
- More environmentally friendly than hydrocarbon solvent based systems Safe to use.
- Non Flammable, non hazardous

Applications:

Use ASP-65 Panel Wipe for surface cleaning/degreasing operations prior to paint application

Use ASP-65 Panel Wipe to clean and degrease surfaces before and after sanding operations.

Use ASP-65 Panel Wipe for de-glazing operations.

Instructions:

Apply the ASP-65 Panel Wipe onto the surface using a lint-free cloth or trigger spray.

Wipe off product applied with a clean and dry lintfree cloth

(NB Do not leave product to flash off on the surface).

Check the surface is completely dry before painting.

Typical Specification:

Composition: A blend of alcohol and ester

solvents in an aqueous base.

Appearance: Water white liquid

Colour : Colourless S.G : 1.00

Shelf Life : Minimum 2 years in unopened

containers at ambient temperature.

Packaging : 5L plastic containers.

ASP-65 is a Trade Mark of Concept Chemicals & Coatings Ltd.

CODE: 70009