

# ALL BLACK GLOSS



**Advanced Paint System:**

Technologically advanced acrylic formulation for durability and flexibility. Suitable for application to both metal and many plastic surfaces.

**Super Coverage:**

High solids formulation gives enhanced coverage allowing for fast turnaround.

**‘Factory’ Match Standard:**

Quality of finish gives professional O.E. standard

**Ideal Guide Coat:**

An ideal ‘guide coat’ for paintshop use.

**Directions for Use:**

Preparation: Prepare surfaces by lightly sanding with wet or dry paper. Ensure that surfaces are clean, dry and free from dirt wax etc.

**CAUTION:** Pressurised container; protect from sunlight. Do not expose to temperatures exceeding 50°C. Do not puncture or incinerate even when empty. Do not spray onto naked flame or any incandescent material.

**Application:**

Shake can vigorously for 2 minutes after the agitator balls are heard moving. Spray from a distance of 10-12" (25-30cm). Apply a light mist (key) coat, leave for 20 seconds, then apply a full cross coat. Allow 10 minutes before any further coats. Leave for 24 hours to harden.

**AFTER USE** Invert can and spray until valve is cleared.

**Typical Specification :**

- Composition : A blend of acrylic resins, pigments, wetting agents, solvents and propellant in aerosol form
- Appearance : Black Paint
- Odour : Ketone Solvent
- F.P. : -40°C
- Can Pressure : 2.75 Bar
- Shelf Life : 2 years at ambient temperature.
- Packaging : 450ml cans.

**CODE: 444**