

CLEAR ACRYLIC LACQUER

Fast:

Fast drying, scratch resistant clear acrylic coating.

Versatile:

Wide range of uses including sealing/overpainting of metal and paintwork (wheel silver etc.).

Protects:

Protects many surfaces from general weathering, mild acid, alkali and chemical attack. Protects controls on vending machines and machinery – also protects against oxidation of aluminium, copper, silver and brass.

Waterproof Coating:

For maps and technical documents.

CAUTION: Pressured Container.

Protect from sunlight. Do not expose to temperatures exceeding 50°C. Do not puncture or incinerate even when empty. Do not spray onto naked flame or any incandescent material.

Directions:

Shake well before use. Spray a thin coat onto a clean dry surface from distance of 20-25cm. Surface will be touch dry in 20 minutes. Repeat as necessary leaving 20 minutes drying time between coats.

Typical Specification :

Composition : A blend of acrylic resins in hydrocarbon solvents, wetting agents and propellant in aerosol form.

Appearance : Colourless

Odour : Ketone Solvent

F.P. : -40°C

Can Pressure : 2.41 Bar

VOC Content : 297g per can

Solubility : Insoluble in water

Shelf Life : Minimum 2 years at ambient temp.

Packaging : 450ml cans.

CODE: 456