

## CLEAR ACRYLIC LACQUER



### Fast:

Fast drying, scratch resistant clear acrylic coating.

### Versatile:

Wide range of uses including sealing/overpainting of metal and paintwork (wheel silver etc.).

### Protects:

Protects many surfaces from general weathering, mild acid, alkali and chemical attack. Protects controls on vending machines and machinery – also protects against oxidation of aluminium, copper, silver and brass.

### Waterproof Coating:

For maps and technical documents.

### CAUTION: Pressured Container.

Protect from sunlight. Do not expose to temperatures exceeding 50°C. Do not puncture or incinerate even when empty. Do not spray onto naked flame or any incandescent material.

### Directions:

Shake well before use. Spray a thin coat onto a clean dry surface from distance of 20-25cm. Surface will be touch dry in 20 minutes. Repeat as necessary leaving 20 minutes drying time between coats.

### Typical Specification :

Composition	: A blend of acrylic resins in hydrocarbon solvents, wetting agents and propellant in aerosol form.
Appearance	: Colourless
Odour	: Ketone Solvent
F.P.	: -40°C
Can Pressure	: 2.41 Bar
VOC Content	: 297g per can
Solubility	: Insoluble in water
Shelf Life	: Minimum 2 years at ambient temp.
Packaging	: 450ml cans.

CODE: 456