

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.03.2021

Revision: 15.03.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** DOMESTIC APPLIANCE WHITE (Gloss)
- **Article number:** 458
- **UFI:** M5V2-0485-U005-HK33
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
 SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
 SU21 Consumer uses: Private households / general public / consumers
- **Application of the substance / the mixture** Coating compound/ Surface coating/ paint
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 Concept Chemicals & Coatings Ltd.
 Felt Court, Windmill Lane Ind.Estate
 Denton, Manchester M34 3RB England
 Tel 00 44 (0)161 335 0213
 Fax 00 44 (0)161 335 0214
- **Further information obtainable from:**
 Concept Chemicals & Coatings
 Ltd. Felt Court, Windmill Lane Ind.Estate Denton,
 Manchester M34 3RB England
 Tel 00 44 (0)161 335 0213
 Fax 00 44 (0)161 335 0214
 kenny@conceptchemicals.com
- **1.4 Emergency telephone number:**
 During working hours GMT 09.00 - 17.00
 Tel: 0044 (0)161 335 0213
 Fax: 0044 (0)161 335 0214

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Acute Tox. 4	H332	Harmful if inhaled.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
 The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.03.2021

Revision: 15.03.2021

Trade name: DOMESTIC APPLIANCE WHITE (Gloss)

(Contd. of page 1)

· **Hazard pictograms** GHS02, GHS07

· **Signal word** Danger

· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 012119471330-49-0000	propan-2-one	25-50%
	⚠ Flam. Liq. 2, H225 ⚠ Acute Tox. 3, H331	
	⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-0000	propane	10-25%
	⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-211947-46-91-32-0000	butane, pure	10-25%
	⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	

(Contd. on page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.03.2021

Revision: 15.03.2021

Trade name: DOMESTIC APPLIANCE WHITE (Gloss)

(Contd. of page 2)

CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene ⚠ Flam. Liq. 3, H226 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	5-10%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-0000	isobutane ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	5-10%
CAS: 111-76-2 EINECS: 203-905-0 Reg.nr.: 01-2119475108-36-0000	2-butoxyethanol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	5-10%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- **After inhalation** Supply fresh air; consult doctor in case of complaints.
- **After skin contact** If skin irritation continues, consult a doctor.
- **After eye contact**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing** Rinse out mouth and then drink plenty of water.

· 4.2 Most important symptoms and effects, both acute and delayed

Headache

Dizziness

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· **Suitable extinguishing agents** CO₂, sand, extinguishing powder. Do not use water.

· For safety reasons unsuitable extinguishing agents

Water.

Water with full jet.

· 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

· 5.3 Advice for firefighters

· **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers /surface or ground water drains.

(Contd. on page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.03.2021

Revision: 15.03.2021

Trade name: DOMESTIC APPLIANCE WHITE (Gloss)

(Contd. of page 3)

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling Risk of serious damage to eyes.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage

· Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

67-64-1 propan-2-one

WEL Short-term value: 3620 mg/m³, 1500 ppm

Long-term value: 1210 mg/m³, 500 ppm

74-98-6 propane

TWA Short-term value: 3600 mg/m³, 2000 ppm

Long-term value: 1800 mg/m³, 1000 ppm

VLE Short-term value: 3600 mg/m³, 2000 ppm

Long-term value: 1800 mg/m³, 1000 ppm

106-97-8 butane, pure

WEL Short-term value: 1810 mg/m³, 750 ppm

Long-term value: 1450 mg/m³, 600 ppm

Carc (if more than 0.1% of buta-1.3-diene)

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm

Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

(Contd. on page 5)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.03.2021

Revision: 15.03.2021

Trade name: DOMESTIC APPLIANCE WHITE (Gloss)

(Contd. of page 4)

75-28-5 isobutane

TWA Short-term value: 3800 mg/m³, 1600 ppm
Long-term value: 1900 mg/m³, 800 ppm

111-76-2 2-butoxyethanol

WEL Short-term value: 246 mg/m³, 50 ppm
Long-term value: 123 mg/m³, 25 ppm
Sk, BMGV

Ingredients with biological limit values:
1330-20-7 xylene

BMGV 650 mmol/mol creatinine
Medium: urine
Sampling time: post shift
Parameter: methyl hippuric acid

111-76-2 2-butoxyethanol

BMGV 240 mmol/mol creatinine
Medium: urine
Sampling time: post shift
Parameter: butoxyacetic acid

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment**

· **General protective and hygienic measures**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Respiratory protection:** Use suitable respiratory protective device in case of insufficient ventilation.

· **Protection of hands:** Rubber gloves

· **Material of gloves:** Nitrile rubber, NBR

· **Penetration time of glove material**

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

· **Eye protection:** Safety glasses

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Aerosol

Colour: White

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/freezing point: undetermined

(Contd. on page 6)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.03.2021

Revision: 15.03.2021

Trade name: DOMESTIC APPLIANCE WHITE (Gloss)

(Contd. of page 5)

Initial boiling point and boiling range: 55 °C	
· Flash point:	-40 °C
· Flammability (solid, gaseous)	Not applicable.
· Ignition temperature:	240.0 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Not determined.
· Explosion limits:	
Lower:	1.5 Vol %
Upper:	13.0 Vol %
· Vapour pressure at 20 °C:	8300.0 hPa
· Density:	Not determined
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
dynamic:	Not determined.
kinematic:	Not determined.
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**
Harmful if inhaled.
- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.

(Contd. on page 7)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.03.2021

Revision: 15.03.2021

Trade name: DOMESTIC APPLIANCE WHITE (Gloss)

(Contd. of page 6)

- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.
Do not allow product to reach ground water or water course.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|---|--|
| <ul style="list-style-type: none"> · 14.1 UN-Number · ADR, IMDG, IATA | UN1950 |
| <ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG · IATA | 1950 AEROSOLS
AEROSOLS
AEROSOLS, flammable |

(Contd. on page 8)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.03.2021

Revision: 15.03.2021

Trade name: DOMESTIC APPLIANCE WHITE (Gloss)

(Contd. of page 7)

· 14.3 Transport hazard class(es)

· ADR



· **Class** 2.5F Gases.
· **Label** 2.1

· IMDG



· **Class** 2 Gases.
· **Label** 2.1

· IATA



· **Class** 2.1
· **Label** 2.1

· 14.4 Packing group

· **ADR, IMDG, IATA** Void

· 14.5 Environmental hazards:

· **Marine pollutant:** No

· 14.6 Special precautions for user

· **Hazard identification number (Kemler code):** -

· **EMS Number:** F-D,S-U

· **Stowage Code**

· Segregation Code

Warning: Gases.

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

SG69 For AEROSOLS with a maximum capacity of 1 litre:

Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.

For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2.

For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of class 2.

· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

(Contd. on page 9)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.03.2021

Revision: 15.03.2021

Trade name: DOMESTIC APPLIANCE WHITE (Gloss)

(Contd. of page 8)

· **Transport/Additional information:**

· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	B1D

· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity

· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1
---------------------------------	-----------------------

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms** GHS02, GHS07

· **Signal word** Danger

· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations**

· **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 10)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.03.2021

Revision: 15.03.2021

Trade name: DOMESTIC APPLIANCE WHITE (Gloss)

(Contd. of page 9)

· **Relevant phrases**

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.

· **Department issuing SDS:** Technical Department.

· **Contact:**

Mr W Broadhurst
Mr N Wardlaw

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Gas 1A: Flammable gases – Category 1A
Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 3: Acute toxicity – Category 3
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3