

EXEL AUTO SILVER



Advanced Paint System:

Technologically advanced acrylic formulation for durability and flexibility. Suitable for application to both metal and plastic wheel trims.

Superfine Finish:

Superfine aluminium to give a quality standard demanded by professional trade users. Gives low gloss sheen. Not Matt.

Excellent Coverage:

Easy to use, rapid coverage. No damp weather problems associated with conventional cellulose systems.

Directions for Use:

Preparation: Prepare surfaces by lightly sanding with wet or dry paper. Ensure that surfaces are clean, dry and free from dirt, oil, wax etc.

CAUTION: Pressurised container; protect from sunlight. Do not expose to temperatures exceeding 50°C. Do not puncture or incinerate even when empty. Do not spray onto naked flame or any incandescent material.

Application:

Shake can vigorously for 2 minutes after the agitator balls are heard moving. Spray from a distance of 10-12" (25-30cm). Apply a light mist coat, leave for 20 seconds, then apply a full cross coat. Allow 10 minutes before any further coats. Leave for 24 hours to harden.

AFTER USE Invert can and spray until valve is cleared.

Typical Specification :

- Composition : A blend of acrylic resins, pigments, wetting agents, solvents and propellant in aerosol form.
- Appearance : Silver paint
- F.P. : -40°C
- Odour : Ketone Solvent
- Can Pressure : 2.75 Bar
- Shelf Life : 2 years ambient temp.
- Packaging : 450ml aerosol can.

Exel Auto Silver is just one of a range of Wheel Silvers manufactured to give a professional choice of colour

CODE: 436