

Printing date 19.02.2021 Revision: 19.02.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: AEROSOL GREY PRIMER
- · Article number: 446
- · UFI: F4JY-M3YT-9009-QWTP
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites SU21 Consumer uses: Private households / general public / consumers

- · Application of the substance / the mixture Coating compound/ Surface coating/ paint
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Concept Chemicals & Coatings Ltd. Felt Court, Windmill Lane Ind.Estate Denton, Manchester M34 3RB England Tel 00 44 (0)161 335 0213 Fax 00 44 (0)161 335 0214

· Further information obtainable from:

Concept Chemicals & Coatings Ltd. Felt Court, Windmill Lane Ind.Estate Denton, Manchester M34 3RB England Tel 00 44 (0)161 335 0213 Fax 00 44 (0)161 335 0214 cheryl@conceptchemicals.com

1.4 Emergency telephone number:

During working hours GMT 09.00 - 17.00

Tel: 0044 (0)161 335 0213 Fax: 0044 (0)161 335 0214

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Acute Tox. 4 H332 Harmful if inhaled.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms GHS02, GHS07

(Contd. on page 2)



Printing date 19.02.2021 Revision: 19.02.2021

Trade name: AEROSOL GREY PRIMER

(Contd. of page 1)

· Signal word Danger

· Hazard-determining components of labelling:

propan-2-one 2-butoxyethanol

xylene

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H332 Harmful if inhaled.

H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P251 Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Keep out of the reach of children

· 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 67-64-1 EINECS: 200-662-2	propan-2-one	25-50%
Reg.nr.: 012119471330-49-0000	Acute Tox. 3, H331 Acute Tox. 4, H302; Acute Tox. 4, H312; Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21- 0000	propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	10-25%

(Contd. on page 3)





Printing date 19.02.2021 Revision: 19.02.2021

Trade name: AEROSOL GREY PRIMER

	(Cont	d. of page 2
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-211947-46-91-32- 0000	butane, pure Flam. Gas 1A, H220 Press. Gas (Comp.), H280	10-25%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27- 0000	isobutane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	5-10%
CAS: 111-76-2 EINECS: 203-905-0 Reg.nr.: 01-2119475108-36- 0000	2-butoxyethanol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	0-2.5%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32- xxxx	xylene Flam. Liq. 3, H226 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	0-2.5%

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation Supply fresh air; consult doctor in case of complaints.
- · After skin contact If skin irritation continues, consult a doctor.
- · After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing Rinse out mouth and then drink plenty of water.
- · 4.2 Most important symptoms and effects, both acute and delayed Headache

Dizziness

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents

Water.

Water with full jet.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)





Printing date 19.02.2021 Revision: 19.02.2021

Trade name: AEROSOL GREY PRIMER

(Contd. of page 3)

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers /surface or ground water drains.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Risk of serious damage to eyes.

Open and handle receptacle with care.

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage

· Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Additional information about design of technical facilities: No further data; see item 7.

Ingredients with limit values that require monitoring at the workplace:

67-64-1 propan-2-one

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

74-98-6 propane

TWA Short-term value: 3600 mg/m³, 2000 ppm Long-term value: 1800 mg/m³, 1000 ppm VLE Short-term value: 3600 mg/m³, 2000 ppm Long-term value: 1800 mg/m³, 1000 ppm

(Contd. on page 5)





Printing date 19.02.2021 Revision: 19.02.2021

Trade name: AEROSOL GREY PRIMER

(Contd. of page 4)

106-97-8 butane, pure

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

75-28-5 isobutane

TWA Short-term value: 3800 mg/m³, 1600 ppm Long-term value: 1900 mg/m³, 800 ppm

111-76-2 2-butoxyethanol

WEL Short-term value: 246 mg/m³, 50 ppm Long-term value: 123 mg/m³, 25 ppm Sk. BMGV

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BMGV 240 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: butoxyacetic acid

1330-20-7 xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment
- General protective and hygienic measures

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- · Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation.
- Protection of hands: Rubber gloves
- · Material of gloves Nitrile rubber, NBR
- Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

· Eye protection: Safety glasses

GB





Printing date 19.02.2021 Revision: 19.02.2021

Trade name: AEROSOL GREY PRIMER

(Contd. of page 5)

9.1 Information on basic physical and of General Information	chemical properties
Appearance: Form: Colour: Odour:	Aerosol According to product specification Characteristic
Odour threshold:	Not determined. Not determined.
pH-value:	NOLUCICITIIIIEU.
Change in condition Melting point/freezing point: Initial boiling point and boiling range	undetermined : > 34 °C
Flash point:	-40 °C
Flammability (solid, gaseous)	Not applicable.
Ignition temperature:	365.0 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Not determined.
Explosion limits: Lower: Upper:	1.5 Vol % 13.0 Vol %
Vapour pressure at 20 °C:	8300.0 hPa
Density: Relative density Vapour density Evaporation rate	Not determined Not determined. Not determined. Not applicable.
Solubility in / Miscibility with Water:	Not miscible or difficult to mix
Partition coefficient: n-octanol/water:	Not determined.
Viscosity: dynamic: kinematic:	Not determined. Not determined.
	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- \cdot 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 7)





Printing date 19.02.2021 Revision: 19.02.2021

Trade name: AEROSOL GREY PRIMER

(Contd. of page 6)

· 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful if inhaled.

- · Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

Do not allow product to reach ground water or water course.

Danger to drinking water if even small quantities leak into the ground.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)





Printing date 19.02.2021 Revision: 19.02.2021

Trade name: AEROSOL GREY PRIMER

(Contd. of page 7)

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name ADR IMDG IATA	1950 AEROSOLS AEROSOLS AEROSOLS, flammable
14.3 Transport hazard class(es) ADR	
Class Label	2 5F Gases. 2.1
IMDG Class	2 Canas
Class Label	2 Gases. 2.1
IATA Class Label	2.1 2.1
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Hazard identification number (Kemler EMS Number:	Warning: Gases. code): - 2-13

(Contd. on page 9)



Printing date 19.02.2021 Revision: 19.02.2021

Trade name: AEROSOL GREY PRIMER

	(Contd. of page 8)
1L	
Code: E0	
Not permitted as Excepted Quantity	
2	
B1D	
1L	
Code: E0	
	Code: E0 Not permitted as Excepted Quantity 2 B1D

Not permitted as Excepted Quantity

UN 1950 AEROSOLS, 2.1, (B1D)

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms GHS02, GHS07
- · Signal word Danger

· UN "Model Regulation":

· Hazard-determining components of labelling:

propan-2-one

2-butoxyethanol

xylene

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H332 Harmful if inhaled.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P251 Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· National regulations

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

(Contd. on page 10)





Revision: 19.02.2021 Printing date 19.02.2021

Trade name: AEROSOL GREY PRIMER

(Contd. of page 9)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

· Department issuing SDS: Technical Department.

· Contact:

Mr W Broadhurst

Mr N Wardlaw

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Acute Tox. 3: Acute toxicity - Category 3 Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3