

## **DATA SHEET**

## LIFT FALL-OUT REMOVER



**Problem Solver:** Lift is a complex blend of acids and surfactants designed to safely remove burnt in particles of rust, metal and industrial fall-out from paintwork on cars, trains, caravans etc.

**Industrial Fall-out:** Contamination of paintwork can occur from overhead electrical sparking on rail transporters, power station acid fall-out, work down roads etc.

Complete Treatment: Lift will remove these contaminants from paintwork, glass, rubber, chrome trim and plastic surfaces\*.

**Directions For Use:** The paintwork must be cool. Do not apply Lift in direct sunlight which can cause the product to dry out.

Apply Lift undiluted with a sponge. Treat one panel at a time ensuring surface does not dry out. Gently wipe the wetted sponge over the surface with plenty of water in the sponge. As soon as fall-out has been removed, rinse off thoroughly with clean water. Ensure complete rinsing taking care to rinse behind plastic or rubber trim where the liquid may dwell. Finally shampoo-wash the complete surface to fully neutralise any remaining solution. If there is any excessively heavy fall-out it may be necessary to repeat the process.

Paint finishes will not be damaged by Lift but it may be necessary to re-polish to regain protection and gloss.

**Important:** When used on glass, perspex, chrome, anodised aluminium and plastic parts. It is necessary to test for suitability prior to general treatment. Using Lift the surfaces being tested must be worked over immediately with sponge and water.

**Rust Remover:** Ideal solution for removing brown rust from door seam edges. Apply to dry rust and allow 10 minutes to react. Do not allow to dry out. Rinse off thoroughly with water.

\*NB. With the increasing use of recycled plastics used in the manufacturer of finished new plastic components, it is first necessary to check that the plastic will not be stained before general treatment; test on a small inconspicuous area.

For a completely Plastic-Safe alternative, there is now available Fall-Out Remover #136.

## **Typical Specification:**

Composition: A complex blend of acids,

surfactants and water.

Appearance : Pale yellow/green liquid

S.G. : 1.18 pH : 1 Odour : Acidic

Shelf Life : Two years in unopened

containers.

Packaging : 5L and 25L drums.

Lift Fall-Out Remover is a Trade Mark of Concept Chemicals & Coatings Ltd

**CODE**: 133