DataSheet

FADE-OUT THINNER

QUICK AND EASY WAY TO BLEND-IN EDGES TO REPAIRED AREAS.

<IDEAL FOR SMART REPAIR>

- A technically advanced blending solvent that dissolves the edges of clear coats and solid colours resulting in the perfect finish.
- Surf-ACE FADE-OUT THINNER is a fast and simple way to accurately dissolve edges on <u>ALL</u> clear coats to give an invisible blend.
- The perfect solution for smart repairs Using this spot repair blender, enables the user to confine repairs to a single panel.

USER INSTRUCTIONS

Once clear coat has been applied to the satisfaction of the painter a light mist coat of Surf-ACE FADE-OUT THINNER is applied over the blend area.

Hold the aerosol 25cm from the panel. Apply two rapid light passes of the aerosol. The blend edge will melt into the original paintwork requiring little or no processing once the clear coat has cured.

Once the Surf-ACE FADE-OUT THINNER is applied, the clear coat manufacturer's instructions for flash off and air/force dry should be followed.

Typical Specification:

Composition: A complex ketone mixture in a blend

of propellants in aerosol form.

Appearance : Colourless Odour : Ketones

Solubility : Insoluble in water

Shelf Life : Minimum 2 years at ambient

temperature.

Packaging : 450ml aerosol can.

VOC Content : 307g/can

CODE: 72012