

ORLD FIRST TECHNOLO

DataSheet

FLAT-MATT

One-Step water based abrasive cleaning and preparation system for preparation of panels for painting, for blending-in of new paintwork when carrying out local repairs and for clear coat preparation.



3-in-1 Saves Time: Triple-action Flatting Paste, abrades, cleans and completely degreases in one easy step.

Consistent even key: enhances coating adhesion by creating smooth even surface preventing any 'swelling' in blend areas. Prevents problems of scratches or tramlines that can sometimes appear through the clear coat.

Easy to apply: Works fast in ideal combination with nylon finishing pads (grey/ultra-fine or copper/superfine) maintaining consistent abrasive action. Can be used with pure cotton cloth for areas around trim or under seals.

Corners and crevices: Uniform matting and cleaning action gives the perfect key in hard-to-reach areas – e.g: doorjambs and sills, drip channels, door locks, handles etc.

Water-based: Easy to wipe off from prepared surfaces, leaving no residues to impair paint adhesion.

No problems: Non-staining on rubber mouldings or trims. Silicone free.

Universal: For use on all today's advanced refinish paint finishes including: Water based, High Solids (HS), Medium Solids (MS) and OEM finishes.

Plastic-Prep – Ideal for cleaning and abrading plastic bumpers and rubber parts prior to painting.

Directions: Shake well before use.

Wash away from surface area any large dirt particles that can cause scratches. Using clean water, <u>dampen</u> the nylon' hand pad; wring-out any excess water. Apply Flat-Matt to hand pad or direct to panel (allowing approximately 10gms. per average sized panel).

Using medium to firm pressure abrade surface using even pad strokes in a criss-cross action, until the panel is thoroughly cleaned and the desired matt finish is obtained.

All pre-treated areas must be wiped down thoroughly with a damp cloth or solvent wipe and dried prior to paint application.

Typical Specification :

Composition	:	A blend of superfine abrasives, cleaning and degreasing agents.
Appearance	:	Paste
Colour	:	Dark grey
pН	:	8.0
S.G	:	1.40
Shelf Life	:	Minimum 2 years in unopened containers at ambient temperature.
Packaging	:	1L plastic containers.

Surf-ACE Flat-Matt is a Trade Mark of Concept Chemicals & Coatings Ltd.

CODE: 70006