



## P-12 XTRA

### HEAVY CUT COMPOUND, SOLUTION FOR AUTOMOTIVE, MARINE & FURNITURE APPLICATIONS

#### Feature benefits:

**Heavy Cutting Compound:** recommended for harder clear-coats which quickly and easily removes paintwork and gelcoat imperfections, random deep scratches, and heavy oxidation in the shortest possible time to enable the end user to deliver a unique depth of gloss mirror like finish.

P-12 XTRA Benefits from an improved lubrication system which can be worked for prolonged periods if required without drying out.

#### Superior Performance:

P-12 XTRA is a specially formulated concentrated compound which benefits from the NEW UNIQUE DRA – (Dynamic response Abrasion) technology. DRA - incorporates (**concentrated**) micro precision oxides for increased cutting power and performance to harder lacquer and gelcoat finishes.

#### For Best Results:

Use with Concept:

XC-15 Micro Wool pad – Heavy Cut

P-15 White Foam - General Purpose

P-30 Orange Foam – Heavy swirl-marks

Machine Speed: 1500-RPM approx (free running)

#### Non-Cosmetic:

P-12 XTRA offers Quick and easy Clean up after application, and it does not contain fillers.

Guarantees minimal drop back on dark colours.

**For use on:** All automotive and Marine paint systems including water based, HS high solid, MS, infrared and accelerator cured paints, single component and 2-pack, acrylic, cellulose, synthetic and OEM finishes including Nano Ceramic Clear Coats.

**Approved:** Ammonia and Silicone Free – Paintable!

**Health & Safety:** Non-flammable.

#### Application:

**Note 1:** Do not over apply or use excessive compound.

**Note 2:** On soft or sensitive paint, or where heat build-up may be a problem, the addition of water mist to avoid any friction burn, particularly with **new pads** may assist in the polishing process. However, avoid unnecessary/excessive water.

**Note 3:** Once a new pad is activated with water no additional water needs to be used once the pad has been impregnated with product.

1. Apply P-12 XTRA in small quantities to paint surfaces (use minimum amount to work required area).
2. Work the surface applying medium pressure until the scratches and imperfections are removed.
3. Reduce pressure as the mop starts to move freely to allow polishing action to take place. After compounding remove any residue and buff surface with clean soft cloth.

Repeat steps 1 to 3 if additional scratch removal is required

#### Typical Specification:

Composition : An emulsion containing inert Polishing agents, emulsifiers and thickeners.

Appearance : White

Odour : Characteristic

pH :  $8.5 \pm 0.5$

F.P. :  $>65^{\circ}\text{C}$

VOC : 175.4g/Kilo

Solubility : Miscible in water

Shelf Life : 2 years minimum in ambient temperature. Protect from frost.

Packaging : 1kg

**For Swirl-mark removal and Gloss Enhancement, P-12XTRA should be followed with the P-40Xtra Finishing Glaze with the relevant pads.**

**CODE: 713**