

SURGE

ACID DESCALING FLUID & CONCRETE CLEANER



Specially Formulated:

For the fast and efficient descaling of all steam cleaning and power wash plant – heating coils etc.

Removes:

Removes dried-on concrete/cement and plaster splashes from paintwork, plant and equipment.

Cleans:

Brickwork, stone, concrete paving slabs, quarry tiles etc.

Derusts:

Derusts ferrous metals prior to painting. N.B. Not suitable for non-ferrous metals.

Directions For Use:

De-Scaling pressure cleaners: Dilute Surge with up to 10 parts water in the machine header tank. Circulate the solution by placing the lance in the header tank. Continue this process for 10 minutes then flush completely through with clean water to remove all traces of descaler. The metal parts must be rinsed thoroughly or damage may occur.

Concrete Removal/Brickwork Cleaning

To remove concrete/cement deposits and for brickwork cleaning mop or brush Surge neat or dilute up to 1 –10 with clean water. Allow time for the deposits to be dissolved then rinse off completely with clean water. Do **NOT** allow acid to dry on to paint surfaces as damage may occur. KEEP SOLUTION WET.

Descaling Metal:

Dilute with 4 parts water. Brush on, allow to descale, rinse and allow to dry, then paint or protect from corrosion immediately.

Typical Specification :

Composition : A powerful blend of wetting agents, inhibitors and hydrochloric acid having a powerful descaling action.

Appearance : Clear liquid

Colour : Slight Straw

S.G. : 1.09

Odour : Slight almond

pH : 1

Shelf Life : 2 years in unopened containers.

Packaging : 5L & 25L plastic containers.

CODE: 122