

Page 1/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.05.2023

Revision: 24.05.2023

undertak	
1.1 Produc	
	e: ZIRCONITE PANEL-PREP
UFI: M6D1 1.2 Releva Sector of U SU3 Indus Applicatio	strial uses: Uses of substances as such or in preparations at industrial sites n of the substance / the mixture gent/ Cleaner
1.3 Details	of the supplier of the safety data sheet
tlf:+45 7020 fax: +45 70 info@bellac 1.4 Emerg	20 7759
SECTION	
2.1 Classif	I 2: Hazards identification ication of the substance or mixture ion according to Regulation (EC) No 1272/2008
2.1 Classificat Classificat flam. Liq. 2	ication of the substance or mixture ion according to Regulation (EC) No 1272/2008 ame 2 H225 Highly flammable liquid and vapour. prrosion
2.1 Classificat Classificat flam. Liq. 2 Flam. Liq. 2 Eye Dam.	ication of the substance or mixture ion according to Regulation (EC) No 1272/2008 ame 2 H225 Highly flammable liquid and vapour. prrosion 1 H318 Causes serious eye damage.
2.1 Classificat Classificat Flam. Liq. 2 Eye Dam. 2.2 Label e Labelling a The produc	ication of the substance or mixture ion according to Regulation (EC) No 1272/2008 ame 2. H225 Highly flammable liquid and vapour. Derrosion 1. H318 Causes serious eye damage. I H318 Causes serious eye damage. Idements Inccording to Regulation (EC) No 1272/2008 t is classified and labelled according to the GB CLP regulation. tograms GHS02, GHS05
2.1 Classificat Classificat Flam. Liq. 2 Eve Dam. 2.2 Label e Labelling a The produc Hazard pic Signal wor Hazard-de ethyl (S)-2-	ication of the substance or mixture ion according to Regulation (EC) No 1272/2008 ame 2. H225 Highly flammable liquid and vapour. Derrosion 1. H318 Causes serious eye damage. I tis classified and labelled according to the GB CLP regulation. tograms GHS02, GHS05 d Danger termining components of labelling: hydroxypropionate
2.1 Classificat Classificat Flam. Liq. 2 Flam. Liq. 2 Eye Dam. 2.2 Label e Labelling a The produc Hazard pic Signal wor Hazard-de ethyl (S)-2- Hazard sta H225 Highl H318 Caus Precautior	ication of the substance or mixture ion according to Regulation (EC) No 1272/2008 ame 2: H225 Highly flammable liquid and vapour. prrosion 4: H318 Causes serious eye damage. Hements focording to Regulation (EC) No 1272/2008 t is classified and labelled according to the GB CLP regulation. tograms GHS02, GHS05 d Danger termining components of labelling: hydroxypropionate tements y flammable liquid and vapour. es serious eye damage.
2.1 Classificat Classificat Flam. Liq. 2 Flam. Liq. 2 Eye Dam. 2.2 Label e Labelling a The produc Hazard pic Signal wor Hazard-de ethyl (S)-2- Hazard sta H225 Highl H318 Caus	ication of the substance or mixture ion according to Regulation (EC) No 1272/2008 ame 2: H225 Highly flammable liquid and vapour. prrosion 4: H318 Causes serious eye damage. Hements incoording to Regulation (EC) No 1272/2008 t is classified and labelled according to the GB CLP regulation. tograms GHS02, GHS05 d Danger termining components of labelling: hydroxypropionate terminis y flammable liquid and vapour. es serious eye damage.



Page 2/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.05.2023

Revision: 24.05.2023

Trade name: ZIRCONITE PANEL-PREP

	(Contd. of page 1)
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P243	Take action to prevent static discharges.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353	B IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338	<i>B</i> IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/ international regulations.
2 2 Othor hazard	

2.3 Other hazards

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

CAS: 64-17-5	ethanol	50-100%	
EINECS: 200-578-6 Reg.nr.: 01-2119457610-43	 Flam. Liq. 2, H225 Eye Irrit. 2, H319 		
CAS: 687-47-8	ethyl (S)-2-hydroxypropionate	10-25%	
EINECS: 211-694-1	 Flam. Liq. 3, H226 Eye Dam. 1, H318 STOT SE 3, H335 		
CAS: 107-98-2	monopropylene glycol methyl ether	5-10%	
EINECS: 203-539-1 Reg.nr.: 01-2119457435-35- 0000	 Flam. Liq. 3, H226 STOT SE 3, H336 		
CAS: 67-56-1	methanol	0-2.5%	
EINECS: 200-659-6 Reg.nr.: 01-2119433307-44	 Flam. Liq. 2, H225 Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 STOT SE 1, H370 		

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- · After inhalation Supply fresh air; consult doctor in case of complaints.
- After skin contact Generally the product does not irritate the skin.

GB



Page 3/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.05.2023

Revision: 24.05.2023

Trade name: ZIRCONITE PANEL-PREP

• After eye contact

(Contd. of page 2)

- Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

- · Suitable extinguishing agents
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 6.2 Environmental precautions: Prevent seepage into sewage system, workpits and cellars.
- Dilute with plenty of water.
- Do not allow to enter sewers /surface or ground water drains.
- 6.3 Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders). Ensure adequate ventilation.
- 6.4 Reference to other sections See Section 7 for information on safe handling See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Risk of serious damage to eyes. Prevent formation of vapours Risk of serious damage to eyes.
 Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- 7.2 Conditions for safe storage, including any incompatibilities

Storage

- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.

(Contd. on page 4)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.05.2023

Trade name: ZIRCONITE PANEL-PREP

• Further information about storage conditions: Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see section 7.

64-17	-5 ethanol	
WEL	Long-term val	ue: 1920 mg/m³, 1000 ppm
		bylene glycol methyl ether
WEL	Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Sk	
67-56	5-1 methanol	
WEL	Short-term value: 333 mg/m³, 250 ppm Long-term value: 266 mg/m³, 200 ppm Sk	
· DNEI	Ls	
64-17	-5 ethanol	
Oral	LD50	>2,000 mg/kg (rat)
Derm	al LD50	>2,000 mg/kg (rab)
Inhala	ative LC50/4 h	>20 mg/l (rat)
· Addi	tional informa	tion: The lists valid during the making were used as basis.
 Perse Gene Imme Wash Avoid Resp In case exposition 	diately remove hands before contact with th iratory protec se of brief expo sure use self-co	e equipment and hygienic measures e all soiled and contaminated clothing breaks and at the end of work. he eyes.

(Contd. on page 5)



Page 4/9

Revision: 24.05.2023

(Contd. of page 3)



Page 5/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.05.2023

Revision: 24.05.2023

Trade name: ZIRCONITE PANEL-PREP

(Contd. of page 4)

9.1 Information on basic physical and o	chemical properties
General Information Appearance:	
Form:	Liquid
Colour:	Colourless
Odour:	Alcohol-like
Odour threshold:	Not determined.
pH-value at 20 °C:	7.5
Change in condition	
Melting point/freezing point:	undetermined
Initial boiling point and boiling range	
Flash point:	13 °C
Flammability (solid, gaseous)	Highly flammable.
Auto-ignition temperature:	270 °C
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation o explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	1.5 Vol %
Upper:	15 Vol %
Vapour pressure at 20 °C:	59 hPa
Density at 20 °C:	0.828 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Fully miscible
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
dynamic:	Not determined.
kinematic:	Not determined.
Solvent content:	
Organic solvents:	90.0 %
Solids content:	0.0 %
9.2 Other information	No further relevant information available.

(Contd. on page 6)

GB



Page 6/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.05.2023

Revision: 24.05.2023

Trade name: ZIRCONITE PANEL-PREP

(Contd. of page 5)

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation
- Causes serious eye damage.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- General notes:
- Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water course or
- sewage system.
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

(Contd. on page 7)



Page 7/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.05.2023

Revision: 24.05.2023

Trade name: ZIRCONITE PANEL-PREP

(Contd. of page 6)

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation Do not allow product to reach ground water or water course.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

• Recommended cleansing agents: Water, if necessary together with cleansing agents.

14.1 UN-Number ADR, IMDG, IATA	UN1993
	0111333
14.2 UN proper shipping name	
ADR	1993 FLAMMABLE LIQUID, N.O.S., speci
IMDG	provision 640D (ETHANOL (ETHYL ALCOHOL)) FLAMMABLE LIQUID, N.O.S. (ETHANOL (ETH)
IMDG	ALCOHOL))
ΙΑΤΑ	FLAMMABLE LIQUID, N.O.S. (ETHANOL)
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
,	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	11
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	
EMS Number:	F-E, <u>S-E</u>
Stowage Category	В
14.7 Transport in bulk according to Annex II	
of Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
Transport ostosory	Maximum net quantity per outer packaging: 500 r
Transport category Tunnel restriction code	2 D/E



Page 8/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.05.2023

Revision: 24.05.2023

Trade name: ZIRCONITE PANEL-PREP

(Contd. of page 7)

 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (ETHANOL (ETHYL ALCOHOL)), 3, II

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation.
- · Hazard pictograms GHS02, GHS05
- · Signal word Danger
- Hazard-determining components of labelling:
- ethyl (S)-2-hydroxypropionate
- Hazard statements
- H225 Highly flammable liquid and vapour.
- H318 Causes serious eye damage.
- · Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P243	Take action to prevent static discharges.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353	[.] IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338	B IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/ international regulations

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

(Contd. on page 9)



Page 9/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.05.2023

Revision: 24.05.2023

Trade name: ZIRCONITE PANEL-PREP

· National regulations

(Contd. of page 8)

- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H301 Toxic if swallowed. H311 Toxic in contact with skin. H318 Causes serious eye damage. H319 Causes serious eye irritation. H331 Toxic if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H370 Causes damage to organs. · Department issuing SDS: Technical Department. · Contact: Mr N Wardlaw · Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (UK REACH) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 3: Acute toxicity - Category 3

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3